


DONNEES TECHNIQUES

Courant de charge [A]	100
Type de réseau de bord	pour véhicules 12V
Type de poulie	PVR7
Pince	M8 B+
Connectique	PLUG381

PHOTOS



Bornes	
B+	Positive
D+	Trio (Lamp)

DOCUMENTS

BT-130 Refus des carcasses alternateurs/démarrEURS

APPLICATIONS

ALFA ROMEO		
145 (930) - 2.0 16V Quadrifoglio	155 ch	03.1998 > 01.2001
145 (930) - 2.0 16V T.S.	150 ch	10.1995 > 01.2001
146 (930) - 2.0 16V Quadrifoglio	155 ch	03.1998 > 01.2001
146 (930) - 2.0 16V T.S.	150 ch	10.1995 > 01.2001
155 (167) - 2.0 T.S. 16V (167.A2G)	150 ch	03.1995 > 12.1997
156 (932) - 2.0 16V T.SPARK (932A2)	155 ch	09.1997 > 10.2000
156 Sportwagon (932) - 2.0 16V T.SPARK (932A2)	155 ch	05.2000 > 10.2000
166 (936) - 2.0 T.SPARK (936A3A__)	155 ch	09.1998 > 10.2000
GTV (916C_) - 2.0 T.SPARK 16V (916.C2__)	150 ch	06.1995 >
GTV (916C_) - 2.0 T.SPARK 16V (916.C2C)	155 ch	05.1998 > 08.2000
SPIDER (94-05) (916S_) - 2.0 T.SPARK 16V (916S2C00)	150 ch	06.1995 > 04.2005
FIAT		
BARCETTA (183) - 1.8 16V	130 ch	04.1995 >
LANCIA		
DEDRA (835) - 1.8 16V LE (835FG)	113 ch	03.1996 > 07.1999
DEDRA (835) - 1.8 GT 16V (835EH)	131 ch	03.1996 > 07.1999
DELTA (93-99) (836) - 1.8 i.e. 16V (836AQ)	113 ch	03.1996 > 08.1999
DELTA (93-99) (836) - 1.8 i.e. 16V GT (836AR)	131 ch	03.1996 > 08.1999

 Avant montage, comparez la pièce reçue à celle d'origine afin de vérifier que la bonne pièce a été choisie et peut être montée sur le véhicule. Le non-respect de cette consigne ou des instructions de montage annule la garantie.